

Multitherm Backing

Ceramic Fibre Backing



Product Data Sheet



Multitherm Backing

Ceramic Fibre Backing



Fire resistance
≤ 120 minutes



Working life
30 years



Use
Can be used indoors

Ceramic Fibre Backing

Multitherm Backing is a glass fibre-based, biodegradable ceramic support material that is heat-resistant up to +1260 °C. It is used as support material for the fire-resistant sealing of gaps and joints and in combination with Multisealant A, Multi mastic SP and Multisealant GR.

Multitherm Backing forms part of the Mulcol® Penetration Seal System and the Mulcol® MultiSeal System.

Advantages

- ✓ Fire resistance ≤ 120 minutes
- ✓ Quick and easy application
- ✓ Reduced shrinkage when exposed to heat
- ✓ Low thermal conductivity
- ✓ Noise absorption
- ✓ Free from binder, fumes or atmospheric contamination
- ✓ Free from asbestos
- ✓ Working life of 30 years

Applications

- ✓ Rigid floors
- ✓ Rigid walls
- ✓ Flexible walls

Technical data

Colour	White
Shelf life	Unlimited shelf life, provided it is stored at more than ±5 °C
Working temperature	+1100°C
Density	128 k/m ³
Advice	Use gloves and respiratory protection (see Safety Data Sheet I MSDS)

Packaging

	Dimensions	Box	Pallet	Pallet	Article number
Strip	610 x 45 x 25 mm	15 pieces	96 boxes	1,440 pieces	208015600

Technical documents available

- ✓ Product Data Sheet (PDS)
- ✓ Technical Data Sheet (T DS)
- ✓ Safety Data Sheet (SDS)
- ✓ Installation Manual

Approvals

- ✓ Tested in accordance with EN 1366-3 / EN 1366-4
- ✓ Classification in accordance with EN 13501-2
- ✓ Certified in accordance with EAD 350454-00-1104/1106
- ✓ ETA report 20/1322, 23/0052, 23/0055 and 23/0060

The above documents are available from your Mulcol contact or via www.mulcol.com



